



## Technical Data Sheet

**RC-70**

### PRODUCT DESCRIPTION

A water based coating that has excellent non-abrasive properties use to provide abrasion protection. Can Be glued with both cold set and hot melt adhesives.

Can be applied via rod or blade at the wet end or dry end of corrugator.

### TYPICAL PHYSICAL PROPERTIES

<b>Viscosity</b> .....	<b>400-600 cps</b>
<b>pH</b> .....	<b>7.0-8.0</b>
<b>Solids</b> .....	<b>35%</b>

### HANDLING & STORAGE

<b>Diluent:</b>	Water, if required. Use as received.
<b>Clean up:</b>	Warm water.
<b>Storage container:</b>	Store in a cool, dry area. Product should not be stored in direct sunlight. Product should not be used after freezing.

Components contained in this product conform for use in paper and paperboard coatings under sections 21 CFR 176.170, CFR 121.2526 and 176.180.

Note: The data presented is based upon tests believed to be reliable; however, RapidBond does not guarantee their accuracy or completeness. RapidBond, assumes no responsibility for results obtained or for incidental or consequential damages arising from the use of this data

#### RapidBond Guarantee

If any product is defective in workmanship or materials, RapidBond, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. RapidBond, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.

#### Contact:

**(619) 423-9943**

**[info@RapidBond.net](mailto:info@RapidBond.net)**

**1579-A JAYKEN WAY • CHULA VISTA, CA 91911**